

## Fine Boring Head Set BT40-Range 8-280mm (0.01mm)

## Spare Shank for Fine Boring Head: BT 50 Taper



Model	Boring Range	Min Graduation	Max Offset	Weight
NBH2084	8-280MM	0.01MM /	28.0MM	3.0

Boring Cutter	Boring Range	DM	Insert	Bolt	Wrench	Weight
BJ2208-32	8 - 11	32	TBGT060102L	SB-1STR-M2	T6	0.095
BJ2010-40	10 - 13	40				0.095
BJ2012-53	12 - 17	53	TBGH090202L	SB-2STR-M2.5	T8	0.12
BJ2016-68	16 - 21	68				0.16
BJ2020-83	20 - 130	83	TPGH110302L	SB-3STR-M3	T8	0.22
BJ2025-96	25 - 135	96				0.34
BJ2030-115	30 - 140	115				0.54
BJ20-20	120 - 280	84 + BT bar				0.23

## Fine Boring Head Set BT40- Range 8-204mm (0.005mm)



BORING CUTTER	BORING RANGE	DM	INSERT	SCREW	WRENCH
SBJ 1608	8-38.	32	TBGH 0601 L	M2	T-6
SBJ 1612	12-42.	53	TBGH0902 L	M2.5	T-8
SBJ 1620	20-50.	83	TBGH1103 L	M3	T-10
SBJ 1645	45-75	90	TBGH1103 L	M3	T-10
NO.1	74-103	-	TBGH1103 L	M2	T-6
NO.2	99-128	-	TBGH1103 L	M2	T-6
NO.3	124-153	-	TBGH1103 L	M2	T-6
NO.4	147-176	-	TBGH1103 L	M2	T-6
NO.5	172-203	-	TBGH1103 L	M2	T-6

Model	Accuracy	Boring Range	Adjustment Precision	Adjust the Stroke
NBH2084S	≤0.005MM	∅8-∅280MM	∅0.005MM	∅30.00MM

## Spare Shank for Fine Boring Head: BT 50 Taper

